


## Ø 108 N

Bearing 6206  
(30 X 62 X 16)

d = 30  
ch = 22  
s = 3,5  
e = 4  
g = 12

belt	roller										
	width mm	dimensions mm			weight Kg		load capacity daN				
arrangements				rotating parts		belt speed m/s					
	B	C	A	parts	total	1	1.5	2	2.5	3	3.5
800	315	323	347	4.3	6.3	406	355	323	299	282	268
1000	380	388	412	4.9	7.2	406	355	323	299	282	268
800 1200	465	473	497	5.7	8.4	406	355	323	299	282	268
1400	530	538	562	6.3	9.4	406	355	323	299	282	268
1000 1600	600	608	632	6.9	10.4	406	355	323	299	282	268
1200	700	708	732	7.8	11.9	406	355	323	299	282	268
1400	800	808	832	8.7	13.3	406	355	323	299	282	268
1600	900	908	932	9.6	14.8	406	355	323	299	282	268
800	950	958	982	10.1	15.5	406	355	323	299	282	268
1000	1150	1158	1182	11.9	18.4	406	355	323	299	282	268
1200	1400	1408	1432	14.2	22.1	406	355	323	299	282	268
1400	1600	1608	1632	16.0	25.0	402	355	323	299	282	268
1600	1800	1808	1832	17.8	27.9	366	355	323	299	282	268

The indicated load capacity relates to a project working life of 30,000 hours.

**Example of ordering**  
standard design  
PSV4,30F,108N,958

for special design  
see pages 80-81