

GAMMA MOTOTAMBURI STANDARD

		GAMMA DI MOTOTAMBURI INDUSTRIALI LEGGERI		GAMMA DI MOTOTAMBURI INDUSTRIALI						
		80LP	113LP	80LS	113LS	138LS	165LS	216LS	220M	220H
Diametro [mm]		85.5	113.6	81.5	113.0	138.5	165	216	216	216
Potenza [kW]	da	0.06	0.06	0.035	0.035	0.1	0.11	0.37	0.37	0.37
	a	0.12	0.37	0.16	0.55	1.00	2.20	2.20	4.00	5.50
Coppia [Nm]	da	7.0	5.0	4.8	8.8	29	30	28	30	115
	a	29	75	30	106	168	340	333	409	705
Forza tangenziale [N]	da	127	87	120	155	345	360	264	279	2093
	a	500	1000	729	1877	2425	4100	3104	4195	6558
Velocità nastro [m/s]	da	0.07	0.03	0.10	0.05	0.05	0.05	0.16	0.2	0.13
	a	0.77	1.05	1.00	1.50	1.60	3.15	4.00	2.50	2.50
Lunghezza RL [mm]	da	253	256	200	250	300	350	350	400	450
	a	912	1212	1000	1200	1800	2000	2000	2000	2000

