




3 Troughing sets

3.2.1 - Choice of the transom in relation to load

Tab. 23 - Capacity of standard transom

belt width mm	type of transom and diameter of suitable rollers			
	A2 S-20°  Ø 60÷110 Kg	A3 L-30°  Ø 76÷110	A3 M-30°  Ø 89÷110 Ø 133÷140	
300	338			
400	286	286		
500	205	247	247	247
650	167	205	205	205
			354	354
800	167	167	289	289
			460	460
1000			244	244
			388	388
1200			204	204
			325	325
1400				
1600				
1800				
2000				
2200				

A3 P-30°




Ø 89÷108

Ø 108÷133

Ø 133÷159

A3 S-35°



Ø 133

Ø 159

Ø 194

R2 S-10°



Ø 89÷180

									354
	289	289	289	289	289				289
	460	460	460	460	460				
	244	244	244	244					
	388	388	388	388	388				388
		581	581	581	581				
	204	204	204	204					
	325	325	325	325	325				325
		487	487	487	487				
				634	634				
		288	288	431	431				431
		431	431	561	561				561
		561	561	710	710				
		387	387	387	387				387
		503	503	503	503	503			503
				637	637	753			
			446	446	446	446			342
			667	667	667	667			446
					604	604			604
					909	909			
					558	558			
					840	840			