


OIL CONTENTS IN LITER FOR STANDARD Motorized Pulleys in HORIZONTAL applications




RL	138LS	165LS	220M & 220H		320M & 320H			400M	400H	500H	630M	630H	800M	800H	800HD	1000H	1000HD
			0.37-0.55kW 1.1-1.5kW	0.75kW 2.2-5.5kW	0.75k- 3.0kW	4.0 - 5.5kW	7.5kW 11.0kW										
300	0.7																
350	0.9	1.2															
400	1.1	1.4	3.00														
450	1.3	1.6	3.50	4.00													
500	1.5	1.8	4.00	5.00	3.50	8.0	10.0										
550	1.8	2.0	4.25	5.25	3.75	8.5	10.5										
600	2.0	2.3	4.50	5.50	4.00	9.0	11.0										
650	2.2	2.5	4.75	5.75	4.25	9.5	12.0	8.5	17.0								
700	2.4	2.7	5.00	6.00	4.50	10.0	13.0	9.0	18.0								
750	2.6	2.6	5.25	6.25	5.00	10.5	13.5	9.5	19.0	11.5	27.5						
800	2.8	3.1	5.50	6.50	5.50	11.0	14.0	10.0	20.0	12.0	28.0						
850	3.0	3.3	5.75	6.75	5.75	11.5	15.0	10.5	21.0	12.5	29.0						
900	3.2	3.5	6.00	7.00	6.00	12.0	16.0	11.0	22.0	13.0	30.0						
950	3.4	3.7	6.25	7.25	6.25	13.0	17.0	11.5	23.0	14.0	32.0	51.5	61.5				
1000	3.6	3.9	6.50	7.50	6.50	14.0	18.0	12.5	25.0	15.0	34.0	53.0	64.0				
1050	3.6	4.1	6.75	7.75	6.75	14.5	18.5	13.5	27.0	15.5	36.0	54.0	66.5				
1100	3.8	4.4	7.00	8.00	7.00	15.0	19.0	14.0	28.0	16.0	38.0	56.5	69.0				
1150	4.0	4.6	7.25	8.25	7.50	16.5	20.5	14.5	29.0	17.0	40.0	59.0	71.0	126.0			
1200	4.2	4.8	7.50	8.50	8.00	18.0	23.0	15.0	30.0	18.0	42.0	60.5	73.0	128.0			
1250	4.4	5.0	7.75	8.75	8.50	19.0	24.0	15.5	31.0	18.5	43.5	63.0	74.5	130.0			235,0
1300	4.6	5.2	8.00	9.00	9.00	20.0	25.0	16.0	32.0	19.0	45.0	64.5	76.0	132.0	130.0		245,0
1350	4.8	5.4	8.25	9.25	9.50	21.0	26.5	17.0	34.0	20.0	46.5	66.0	78.0	134.0	133.0		255,0
1400	5.0	5.6	8.50	9.50	10.00	22.0	28.0	18.0	36.0	21.0	48.0	68.0	80.0	135.0	135.0		268,0 250,0
1450	5.1	5.8	8.75	9.75	10.50	23.0	29.0	18.5	37.0	21.5	49.0	70.0	82.0	137.5	138.0		279,0 260,0
1500	5.3	6.0	9.00	10.00	11.00	24.0	30.0	19.0	38.0	22.0	50.0	72.0	84.0	140.0	140.0		290,0 270,0
1550	4.8	5.8	9.25	10.25	12.00	25.0	31.5	19.5	39.0	23.0	51.5	74.0	86.0	142.5	143.0		301,0 285,0
1600	5.0	6.0	9.50	10.50	13.00	26.0	33.0	20.0	40.0	24.0	53.0	76.0	88.0	145.0	145.0		312,0 300,0
1650	5.1	6.2	10.00	11.00	14.00	27.0	34.0	20.5	41.0	25.0	54.0	79.0	90.0	147.5	148.0		323,0 313,0
1700	5.3	6.4	11.50	11.50	15.00	28.0	35.0	21.0	42.0	26.0	55.0	80.5	92.0	150.0	150.0		334,0 324,0
1750	5.5	6.6	12.00	12.00	16.00	29.0	36.0	22.0	44.0	27.0	56.5	82.0	94.0	152.5	153.0		345,0 335,0
1800	5.6	6.8	13.00	13.00	17.00	30.0	37.0	23.0	46.0	28.0	58.0	84.0	96.0	155.0	155.0		356,0 346,0
1850	5.8	7.0	13.50	13.50	18.00	30.5	38.5	23.5	47.0	30.0	59.5	86.0	98.0	157.5	158.0		367,0 357,0
1900	5.9	7.1	14.00	14.00	19.0	31.0	40.0	24.0	48.0	32.0	61.0	88.0	100.0	160.0	160.0		378,0 368,0
1950		7.3	15.50	14.50	20.0	31.5	40.5	24.5	49.0	34.0	61.5	90.0	102.0	162.0	162.0		389,0 379,0
2000		7.5	15.00	15.00	21.0	32.0	41.0	25.0	50.0	36.0	62.0	92.0	104.0	164.0	164.0		400,0 390,0

Please Note! The given oil contents are valid for STANDARD un-lagged Motorized Pulleys only!
For SPECIAL options the oil contents might deviate severely. Therefore, ALWAYS use the given oil quantity listed on the MOTOR DATA PLATE!

OIL CONTENTS IN LITER (L) FOR SPECIAL CONSTRUCTIONS

Vertical applications



liters (l)

Type	Amount of oil in liter (l)	Specifications
138LS	1.4	Electrical connection to be located at the top
165LS	3.0	
220M	10.0	
220H	10.0	
320M	25.0	
320H	25.0	

Please Note!

- The given oil contents are valid for STANDARD un-lagged Motorized Pulleys only!
- For SPECIAL options the oil contents might deviate severely.
- Therefore, ALWAYS use the given oil quantity listed on the DATA PLATE!

Special Version - Please contact Rulmeca



liters (l)

Please note the indicated oil fill quantities are valid only for STANDARD execution Motorized Pulleys. With SPECIAL executions it is possible that the oil quantities vary. In such a case the given quantities on the motor data label is the valid indication

Product range Motorized Pulleys	Non-horizontal installation between	Typical application	Precautions
138LS & 165LS 220M & 220H 320M & 320H	5° - <90°	Magnetic Separations	Special design & special amount of oil! Please contact Rulmeca before placing the order.

Oil Types

Type of Motorized Pulley	IEC34 Ins.Class	Ambient Temp.	ISO 3498 - DIN 51519	DIN 51517	Castrol	BP	Esso Mobil	Shell	Texaco
Ø138-800 Standard	F	-25°C+40°C	CC ISOVG 150	CLP ISOVG 150	ALPHA SP 150	ENERGOL GR-XP 150	MOBILGEAR 600 XP 150	OMALA 150	MEROPA 150
Ø138-1000 Synthetic option	F	-25°C+40°C	CC ISOVG 220	CLP ISOVG 220	ALPHA-SYN T 220		SHC 630V 220		
Ø138-1000 Standard	H	-25°C+40°C	CC ISOVG 220	CLP ISOVG 220	ALPHA-SYN T 220		SHC 630V 220		
Ø138-800 Food Grade	F & H	-30°C+40°C	CC ISO VG 220	Complies with Food Additive regulation 12 CPR				Shell Cassida GL220	

Synthetic oil is **not only** used for Insulation Class H, but also

- To reduce wear of gears and bearings and consequently increase the service life of the Pulley
- To reduce noise
- To reduce oil damages due to overheating in connection with certain options, types of rubber lagging etc. etc.