



Mototamburi 500L & 500M, Ø 500 mm

50 Hz

| Motore | | Stadi riduttore n. | Velocità nominale a pieno carico a 50 Hz m/sec | Coppia Nm | Forza tan-genz. N | Max. carico radiale T1+T2 N | RL min. speciale | Tipo | Peso in kg per dimensioni STANDARD | | | | | | | | | | Tipo si supporto |
|-----------------|---------|--------------------|--|-----------|-------------------|-----------------------------|------------------|------|---|-----|-----|-----|-----|-----|-----|-----|------|-----------------------|------------------|
| Potenza kW/HP | Poli n. | | | | | | | | RL in mm (RL >2000 mm disponibile su richiesta) | | | | | | | | | | |
| | | | | | | | | | 600 | 650 | 700 | 750 | 800 | 850 | 900 | 950 | 1000 | per 50 mm fino a 2000 | |
| 2.20/ 3.00 | 8 | 3 | 0.20 | 2613 | 10542 | 42200 | 650 | 500M | | 258 | 265 | 272 | 279 | 286 | 293 | 300 | 307 | 7 kg | KL60 |
| | | | 0.25 | 2090 | 8360 | | | | | | | | | | | | | | |
| | | | 0.32 | 1633 | 6532 | | | | | | | | | | | | | | |
| | | 2 | 0.40 | 1306 | 5224 | 35000 | 600 | 500L | 216 | 223 | 230 | 237 | 244 | 251 | 258 | 265 | 272 | | |
| | | | 0.50 | 1045 | 4180 | | | | | | | | | | | | | | |
| | | | 0.63 | 829 | 3316 | | | | | | | | | | | | | | |
| 4.00/ 5.50 | 8 | 3 | 0.32 | 2969 | 11876 | 42200 | 650 | 500M | | 267 | 274 | 281 | 288 | 295 | 302 | 309 | 316 | 7kg | KL60 |
| | | | 0.40 | 2375 | 9500 | | | | | | | | | | | | | | |
| | | | 0.50 | 1900 | 7600 | | | | | | | | | | | | | | |
| | | 2 | 0.63 | 1508 | 6032 | 35000 | 600 | 500L | 225 | 232 | 239 | 246 | 253 | 260 | 267 | 274 | 281 | | |
| | | | 0.80 | 1188 | 4752 | | | | | | | | | | | | | | |
| | | | 1.00 | 950 | 3800 | | | | | | | | | | | | | | |
| 5.50/ 7.50 | 4 | 3 | 0.50 | 2612 | 10448 | 42200 | 650 | 500M | | 258 | 265 | 272 | 279 | 286 | 293 | 300 | 307 | 7 kg | KL60 |
| | | | 0.63 | 2073 | 8292 | | | | | | | | | | | | | | |
| | | | 0.80 | 1632 | 6528 | | | | | | | | | | | | | | |
| | | 2 | 1.00 | 1306 | 5214 | 35000 | 600 | 500L | 216 | 223 | 230 | 237 | 244 | 251 | 258 | 265 | 272 | | |
| | | | 1.25 | 1045 | 4180 | | | | | | | | | | | | | | |
| | | | 1.60 | 816 | 3264 | | | | | | | | | | | | | | |
| 7.50/ 10.00 | 6 | 3 | 0.63 | 2827 | 11308 | 42200 | 710 | 500M | | | | 278 | 285 | 292 | 299 | 306 | 313 | 7 kg | KL60 |
| | | | 0.80 | 2226 | 8904 | | | | | | | | | | | | | | |
| | | | 1.00 | 1781 | 7124 | | | | | | | | | | | | | | |
| | 4 | 2 | 1.25 | 1425 | 5700 | 35000 | 600 | 500L | 222 | 229 | 236 | 243 | 250 | 257 | 264 | 271 | 278 | | |
| | | | 1.60 | 1113 | 4452 | | | | | | | | | | | | | | |
| | | | 2.00 | 891 | 3564 | | | | | | | | | | | | | | |
| 11.00/ 15.00 | 4 | 3 | 1.00 | 2612 | 10448 | 42200 | 710 | 500M | | | | 290 | 297 | 304 | 311 | 318 | 325 | 7 kg | KL60 |
| | | | 1.25 | 2090 | 8630 | | | | | | | | | | | | | | |
| | | | 1.60 | 1633 | 6532 | | | | | | | | | | | | | | |
| | | 2 | 2.00 | 1306 | 5224 | 35000 | 660 | 500L | 216 | 223 | 230 | 237 | 244 | 251 | 258 | 265 | 272 | | |
| | | | 2.50 | 1045 | 4180 | | | | | | | | | | | | | | |
| | | | 3.15 | 829 | 3316 | | | | | | | | | | | | | | |
| 15.00/ 20.00 | 2 | 3 | 1.25 | 2850 | 11400 | 42200 | 710 | 500M | | | | 290 | 297 | 304 | 311 | 318 | 325 | 7 kg | KL60 |
| | | | 1.60 | 2227 | 8908 | | | | | | | | | | | | | | |
| | | | 2.00 | 1782 | 7128 | | | | | | | | | | | | | | |
| | | 2 | 2.50 | 1425 | 5700 | 35000 | 660 | 500L | 216 | 223 | 230 | 237 | 244 | 251 | 258 | 265 | 272 | | |
| | | | 3.15 | 1131 | 4524 | | | | | | | | | | | | | | |

| Tamburo folle | 40500 | 600 | UT400M | 113 | 119 | 126 | 132 | 138 | 142 | 148 | 154 | 160 | 7 kg | KL60 |
|---------------|-------|-------|--------|--------|-----|-----|-----|-----|-----|-----|-----|-----|------|------|
| | | 50000 | 650 | UT400H | | 124 | 131 | 137 | 143 | 147 | 153 | 159 | 165 | 7 kg |