



## 2 Rollers

### series Self cleaning



The rubber rings are held in position at either end by a steel ring welded to the tube.

## Øe 133 NM

Base roller:

### MPS/1

D = 89;  
spindle 15; d<sub>1</sub> = 20  
bearing 6202  
ch = 17

### PSV/1-FHD

D = 89;  
spindle 20; d<sub>1</sub> = 20  
bearing 6204  
ch = 14

### PSV/3-FHD


D = 89;  
spindle 25; d<sub>1</sub> = 25  
bearing 6305  
ch = 18

### PSV/4-FHD

D = 89;  
spindle 30; d<sub>1</sub> = 30  
bearing 6206  
ch = 22

### PSV/2-FHD

D = 89;  
spindle 25; d<sub>1</sub> = 25  
bearing 6205  
ch = 18

belt	roller					weight Kg		rings width E = 38,5		
	width mm	dimensions mm								
arrangement	B	C	A		MPS/1	PSV/1-FHD	PSV/2-FHD	PSV/3-FHD	PSV/4-FHD	L
			MPS/1 PSV/1-FHD	PSV/2-FHD PSV/3-FHD PSV/4-FHD						
400	500	508	526	532	7.3	8.2				460
500	600	608	626	632	8.6	9.5				540
650	750	758	776	782	10.7	11.8	13.3			695
800	950	958	976	982	13.7	15.0	16.5			925
1000	1150	1158	1176	1182	16.2	17.7	19.5	19.9	22.0	1080
1200	1400	1408	1426	1432		21.4	23.5	23.9	26.5	1385
1400	1600	1608		1632			26.5	26.9	29.8	1540
1600	1800	1808		1832			29.5	29.8	33.0	1760

#### Example of ordering

standard design  
PSV/1-FHD,20F,133NM,758

for special designs  
see pages 80-81