



2 Rollers

series

Self cleaning



The rubber rings are held in position at either end by a steel ring welded to the tube.

Øe 133 NM

Base roller:

MPS 1

D = 89;
spindle 15; d₁ = 20
bearing 6202
ch = 17

PSV 1

D = 89;
spindle 20; d₁ = 20
bearing 6204
ch = 14

PSV 2


D = 89;
spindle 25; d₁ = 25
bearing 6205
ch = 18

PSV/3-FHD

D = 89;
spindle 25; d₁ = 25
bearing 6305
ch = 18

PSV/4-FHD

D = 89;
spindle 30; d₁ = 30
bearing 6206
ch = 22

belt	roller					weight					rings width E = 38,5
	width mm	dimensions mm				Kg					
arrangement 	B	C	A		MPS 1	PSV 1	PSV 2	PSV/3-FHD	PSV/4-FHD	L	
			MPS 1 PSV 1	PSV 2 PSV 3 PSV 4							
400	500	508	526	532	7.3	8.2				460	
500	600	608	626	632	8.6	9.5				540	
650	750	758	776	782	10.7	11.8	13.3			695	
800	950	958	976	982	13.7	15.0	16.5			925	
1000	1150	1158	1176	1182	16.2	17.7	19.5	19.9	22.0	1080	
1200	1400	1408	1426	1432		21.4	23.5	23.9	26.5	1385	
1400	1600	1608	1632				26.5	26.9	29.8	1540	
1600	1800	1808	1832				29.5	29.8	33.0	1760	

Example of ordering
standard design
PSV1,20F,133NM,758

for special designs
see pages 80-81