

CERTIFICATE OF COMPLIANCE

Certificate Number 20150618-E471906
Report Reference E471906-20150618
Issue Date 2015-JUNE-18

Issued to: RULMECA GERMANY GmbH
Wilslebener Chaussee 12-14
06449 Aschersleben GERMANY

This is to certify that representative samples of COMPONENT - MOTORS
See Addendum page

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.


Standard(s) for Safety: UL 1004-1, Rotating Electrical Machines – General Requirements;
CSA C22.2 No. 100, Motors and Generators

Additional Information: See the UL Online Certifications Directory at www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's Certification and Follow-Up Service.

Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for use as components of complete equipment submitted for investigation rather than for direct separate installation in the field. The final acceptance of the component is dependent upon its installation and use in complete equipment submitted to UL LLC.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20150618-E471906
Report Reference E471906-20150618
Issue Date 2015-JUNE-18

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Class A Insulated Air Over Motor models tabulated below.

Frame (§)	V	Hz	kW	r/min	Poles	Phase	Enclosure
80	400/460	50/60	0.02	785	8	3	Totally
			0.07	1730	4		
			0.12	3400	2		
113	400/460	50/60	0.07	540	12	3	Totally
			0.15	825	8		
			0.2	1120	6		
			0.37	1700	4		
			0.55	3470	2		
138	525/575	50/60	0.1	550	12	3	Totally
			0.18	840	8		
			0.37	1145	6		
			0.75	1720	4		
			1.0	3470	2		
165 216	525/575	50/60	0.37	580	12	3	Totally
			0.75	1155	6		
			1.5	1730	4		
			2.2	3475	2		
220	525/575	50/60	0.37	575	12	3	Totally
			0.75	845	8		
			1.1	1160	6		
			3.0	1771	4		
			4.0	3521	2		
320	525/575	50/60	0.75	845	8	3	Totally
			1.1	1160	6		
			3.0	1771	4		
			4.0	3521	2		

(§) – may be followed by LS, L, M or H

B. Mahrenholz

Bruce Mahrenholz, Director North American Certification Program
 UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

